SENFENG

www.senfenglaser.com

Laser Blanking Lines

1503CLH

Coiled steel thickness: 0.8-3mm
Working area: 3000*1500mm

- Decoil, level, feed, cut and unload AL and other non-ferrous coiled steels
- Fully-enclosed cutting area to prevent smoke diffusion and worker intrusion by mistake
- Take fully-automatic control of production and adapt to different materials automatically
- Its high-strength machine body will keep indeformable for a long term
- Users prefer to coiled steels to cut-to-length steel plates, so as to lower costs of purchase

1503CLH

Model		1503CLH
Decoiling and Leveling Unit	Size of coiled steels (L*W, mm)	3000*1500
	Thickness of coiled steels (mm)	0.8-3
	Max Inner/Outer Diameter of coiled steels (mm)	Φ508/Φ610 and Φ800-1500
	Weight of coiled steels (T)	15
	Max Feeding Speed (m/min)	15
	Leveling Accuracy (mm^2)	±1.5
Laser Cutting Machine	Laser Power (kW)	6
	X/Y-axis Positioning Accuracy (mm)	±0.05
	X/Y-axis Repositioning Accuracy (mm)	±0.02
Power Supply		Three-phase 380V, 50Hz/60Hz (custom-made)

+86 188 5315 8301 senfeng@sfcnclaser.com